


Front View




Side View


VSF1-MB POWER AND DATA TRACK

Track Used	SFC2 Modular Track
ELECTRICAL	
Rated Current for Pre-wired	13Amp maximum - 3-core 1.5mm ² flexible core cable 16Amp maximum - 3-core 2.5mm ² flexible core cable
Compartment Capacity	Designed to accommodate 4 x Cat5e data cables Designed to accommodate 4 x Cat6 data cables Designed to accommodate 4 x 2.5mm ² flexible core cable
MATERIAL	
Track	Aluminium
Insulation	Polycarbonate


90° Configuration



60° Configuration



SIZE AND WEIGHT (Based on 1 meter Length)	
Dimension (Width x Depth) - 90° Configuration	103mm x 64.6mm
Dimension (Width x Depth) - 60° Configuration	95.3mm x 89.6mm
Weight	Estimated 3.5 kilograms (1m of SFC2 Modular Track with VSF1 Housing and Mounting Base)
Accessories	
	DS3 Data Socket Housing Assembly VSF1 Mounting Base
Guarantee	
	3 years subject to Eubiq Limited Warranty Statement (Applicable to track ONLY)



Front View

SFC2 MODULAR TRACK

ELECTRICAL

Rated Voltage	250V a.c. Single-phase
Rated Current	40Amp maximum
Frequency	50Hz / 60Hz
Conditional Short Circuit Rating	(MCB: In:40A Ue:400V), Type B (BS EN 60898-1) Prospective current: 6KA (BS EN 60439-2)
Conductor Resistance Line & Neutral	4.4 mohm/meter run
Conductor Impedance	4.5 mohm/meter run
Voltage Drop: Line & Neutral Line & Earth	4.5 mV/A/meter run 2.73 mV/A/meter run
Rated Impulse Withstand Voltage	4000V a.c.
Connection of Adaptor or Tap-off Unit	Intended to be connected and disconnected when system is energized and with a load connected
Terminal Capacity: Live, Neutral & Earth	4.0 mm ² to 10 mm ²

ENVIRONMENTAL

Ambient Operating Temperature	-5°C to +40°C (not to exceed an average of more than 35°C in any 24 hours period)
Maximum Installation Altitude	2000 meters
Resistance to Impact	Heavy Impact
Degree of Protection	IP4X
Degree of Pollution	2 (Non-conductive pollution with temporary conductivity caused by condensation)

MATERIAL

Track	Aluminium
Insulation	Polycarbonate

SIZE AND WEIGHT (Based On 1 meter Length)

Overall Dimension (Width x Depth)	63.5mm x 26.8mm
Weight	Estimated 1.8 kilograms

Compliance	IEC 61534-1:2003 ASTA certified
Guarantee	3 years subject to Eubiq Limited Warranty Statement (Applicable to track ONLY)